

# logiJET T6-2

## Ideal for:

- > Stickers, labels and tags up to A5 size
- > RFID inlays (optional)
- > Just-in-time printing or batch processing

## HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- > Easy handling
- > 1D and 2D barcodes
- > IDOL Windows driver included
- > Ethernet (10/100 MBit)
- > Thermal and matrix emulation
- > Automatic switching to active interface & emulation in dependency of interface
- > Optional PCL5e emulation to run directly from SAP

## MAXIMUM FLEXIBILITY FOR SMOOTH PRODUCTION AND LOGISTICS PROCESSES



### logiJET T6-2

The logiJET T6-2 is a robust 6-inch thermal printer, designed to cope with the toughest demands in production and logistics. It prints fast and efficiently on all common materials, either in high-grade thermal transfer quality or with economical and especially efficient direct thermal printing. The logiJET T6-2 features impressive 300dpi resolution enabling, for example, very small barcodes or graphics to be depicted in clear, razor sharp quality. The high performance of the flexible Microplex Controller ensures optimal printing speeds at all times. With optional RFID functionality, UHF RFID inlays can be simultaneously coded during printing.

## Print Engine

<b>Print technology</b>	Thermal transfer/direct thermal harmonic (history-controlled flat head technology)
<b>Controller</b>	MPC 6.6 with ATMEL AT91SAM 9260 (200-MHz-RISC-Prozessor)
<b>Print speed</b>	up to 150 mm/s up to 6 inch/s
<b>Print resolution</b>	300 dpi x 300 dpi
<b>Lifetime print head</b>	Transfer: up to 50.000 m
<b>Power supply</b>	100 - 240 VAC, 50/60 Hz
<b>Power consumption</b>	3,0A
<b>Dimensions (WxDxH in mm)</b>	345 x 516 x 285
<b>Weight</b>	17 kg (without options)
<b>Environment temperature</b>	5 - 35°C
<b>Relative humidity</b>	45 - 75 % (rel., non-condensing)
<b>Interfaces</b>	Serial: USB 2.0 Parallel: IEEE 1284 (Centronics) LAN: Ethernet-Interface 10/100 MBit, bi-directional (TCP/IP) Optional: RS232, RS422
<b>Memory</b>	RAM: 64 MB Flash: 16 MB

## MPC 6.6 High-End Print-Controller

### Emulations

MICROPLEX IDOL, AGFA Reno, LN03+, BULL-MP6090, Datamax (FGL), Etimark MP-1220, TEC Bx72, TEC B6xx, LDC, ZPL II, EPL2, UBI Fingerprint, IER Command, Godex EZPL, Diablo 630, IBM Proprinter, Epson FX-80, MT-600/MT40, IDS, ANSI Genicom, HP Designjet, XML (SAP RFID), CUPS Raster

### Optional Emulations

Factory Option PCL 5e (kann nicht nachträglich freigeschaltet werden),  $\mu$ -Postscript, CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP-10, Datamax Labelpoint, TIFF, IPDS, AEA, AFP, RFM, (more emulations on request)

### Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Strich Datalogic), Interleaved 2/5 (3-Strich Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

### Optional Barcodes

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

### Additional functions

**Intelligent barcode generation** on-the-fly in the printer  
**Format splitting** in several subformats by command

### Optional functions

### Integrated form management

up to 12 MB flash for forms and fonts inside the printer

### Status-Out

gives notice of each correctly printed page via interface

### SPS-Control (EMBEDDED INTELLIGENCE - Enabling two-way communication between printer and a PLC)

integration of the printer into production lines is possible, controlled by SPS-interface.



## Printable Media

### Size

Width	max. 178 mm (165 mm withCutter) printable width 168 mm
roll diameter	max. 203 mm, 3 inch core max. 152 mm, 1,5 inch core
core diameter	1,5 - 3 inch (38,1 - 76,2 mm)

### Paper thickness

0,06 mm - 0,25 mm

### Thermal transfer ribbon

roll diameter	max. 76 mm
<b>Core diameter</b>	1 inch (25.4 mm)
<b>Ribbon length</b>	max. 450 m
<b>Coated side</b>	inside or outside
<b>Ribbon width</b>	60 - 174 mm

## Paper Path

### Input

Continuous	internal from roll external (e.g. fanfold)
------------	---

sensor for black mark and label gap  
(reflection and transmissive)

### Output

Single/Job	tear-off
------------	----------

### Optional

Continuous	internal Peeler / Rewinder
Single	peel-off, Cutter
Job	cutter

### Option RFID

<b>Frequency Range</b>	865.600-867.600 (ETSI EN 302 208)
------------------------	--------------------------------------

### RF Power

programmable in 15 levels (1dB step) from 9dBm to 23dBm (from 8mW to 200mW) conducted

**Standard Protocols** EPC C1 G2 / ISO18000-6C

**Features** read/write/verify (void)

### Registration of antenna position

automatic (depending on antenna design)

The brand names referred to are the registered trademarks of the respective companies. All figures and details in italics and highlighted in color are optional. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 25.04.2017

Microplex Printware AG  
Panzerstraße 5 | 26316 Varel | Germany  
phone +49 4451 91 37-0 | fax +49 4451 91 37-49

