

SOLID 33E-2

MICROPLEX®

**Continuous batch printing
system with optional MICRoner**



Applications

- ... Cheshire labels
- ... label and batch printing
- ... MICR check printing (opt.)

INTEGRATED ON-THE-FLY CUTTING

2 TRACTOR CASSETTES AS STANDARD

WIDE RANGE OF FUNCTIONS

Profitable functions like

- integrated form management
- n-times format splitting
- SPS-Control

by MICROPLEX MPC High-End Controller

HIGH-QUALITY EQUIPMENT

Ethernet and USB already contained
in the basic version

**SAP- UND AS/400-
COMPATIBLE**
by PCL 5e + Jetcaps
and LAN-IPDS

HIGH-END PRINT CONTROLLER

MPC
inside
5.x
FUNCTIONS
EMULATIONS
SPEED

barcodes
1/2D
"on-the-fly"

emulation
IGP

function
integrated
FORM
management

emulation
PCL

ready for...
**PRINT
PLEX**
printmanagement
software

function
SPS
CONTROL

emulation
**MAGNUM
CODE V**

ready for...
LAN-admin.
**IP-
ADMIN**

function
status out
PAGE
CONTROL

emulation
ZPL

ready for...
**SAFE
PRINT**
safe clustering and
printout supervision

control
LAN-admin
**IP-
PANEL**

emulation
**KODE
SCRIPT**

300 dpi
33 pages/minute
16" print width

more than
30
emulations

www.microplex.de

MICRO PLEX
Printware AG
Panzerstraße 5
D-26316 Varel

Tel. +49.4451.9137.0
Fax +49.4451.81063

Email info@microplex.de



PRINTERS



SOFTWARE



AUTOID

MICROPLEX®

SOLID
33E-2

MICROPLEX®

The printing width of 16 inches allows many cheque formats to be printed effectively in two columns. Its print output of up to 33 ppm and a print volume of up to 200.000 pages per month, make it equally well suited to distributed printing applications.

Two individually selectable paper feeds and an integrated paper cutter facilitate the printing of various forms.

SPECIFICATIONS


Print Engine

Print technology	LED, OPC heat/pressure fixing	
Controller	MPC 5.x with Intel XScale PXA 255 (400 MHz RISC processor)	
Print speed	up to 33 pages/minute (A4 landscape) 6,9 m/min	
Resolution	max. 300 dpi x 300 dpi	
Recommended monthly print volume	up to 200.000 pages (based on a using period of 60 months)	
Power supply	240V +10/-6%, 50-60 Hz	
Noise (operating)	< 55 dB (A)	
Dimensions (BxTxH in mm)	890 x 780 x 350	
Environment	relative humidity	30 - 50 %
	temperature	15 - 35°C
Interfaces	serial	USB, RS232, RS422
	parallel	IEEE 1284
	Network	Ethernet-Interface 10/100 MBit, bi-directional (TCP/IP)
Memory	RAM	64 MB
	Flash	16 MB

MPC 5.x High-End Print Controller

Emulations	MICROPLEX IDOL HP PCL 5e Epson FX-80	IBM Proprinter Diablo 630 µ-Postscript TIFF
Optional Emulations	Printronix IGP PGL Express IPDS (more emulations on request)	Magnum Code V Kyocera Prescribe ZPLII, Datamax, EPL (more emulations on request)
Barcodes	EAN 8, 13, 128, add on 2/5 3-stroke Datalogic 2/5 3-stroke Matrix Codabar, PDF 417 Royalbar, Planet	Jetcaps (HP/SAP) Code 39 128 MSI UPC A, E Postnet, KIX USPS One Code
Optional Barcodes	USD5 Aztec-Code (more barcodes on request)	UPS-Maxicode Datamatrix (more barcodes on request)
Functions	Intelligent barcode generation on-the-fly in the printer Format splitting in several subformats by command Integrated form management up to 12 MB flash for forms and fonts inside the printer	
Optional Functions	Status-out gives notice of each correctly printed page via interface SPS-control integration of the printer into production lines is possible, controlled by SPS-interface.	

Paper Path



Feeder/Stacker

Input	2 independent, detachable tractor cassettes	
Output	rear	cutter 3.000 sheet stacker
	top	tray for cut sheets capacity: 100 sheets

Media

Size	form length	3" - 24" with stacker: 7" - 17"
	form width	4" - 17"
	printable area	16"
Weight	64 - 155 g/m ²	

Further Products

Continous printers

SOLID
58E
MICROPLEX®



58
pages/minute
2up mode
300
dpi
6"-18"
form width

SOLID
60E
MICROPLEX®



60
pages/minute
600
dpi
6,5"-16"
form width

SOLID
166E
MICROPLEX®



166
pages/minute
2up mode
600
dpi
7"-18"
form width

www.microplex.de

MICROPLEX
Printware AG
Panzerstraße 5
D-26316 Varel

Tel. +49.4451.9137.0
Fax +49.4451.81063
Email info@microplex.de



PRINTERS



SOFTWARE



AUTOID

Distributeur

T I E SARL
ZA de la Duquerie
F - 37390 CHANCEAUX SUR CHOISILLE
Tél: + 33 (0) 2 47 49 26 76
Fax: + 33 (0) 2 47 49 16 37
Email: contact@tiie.eu
<http://www.tiie.fr>

Product names mentioned here in are trademarks and/or registered trademarks of their respective companies. All prices and specifications may be changed at any time without notice. No promise or guarantee is made as to the accuracy of the specifications provided and furthermore not that the numbers / prices quoted or specified in the final product purchased. It remains to confirm and prove that the specifications of the product meet with the buyers needs for a specific application and/or installation.

MICROPLEX®